

Recessed power and data is preferred for all wall types. In scenarios where power and data cannot be recessed into the wall slim surface mounted device boxes can be

- Recessed power and data is preferred for all wall types. In scenarios where power and data cannot be recycled into the wall, slim surface mounted device boxes can be used. Surface mounted conduit can also be used but must be routed straight down to the specified power and data location. **Legrand Wiremold 151/16" deep boxes with 500/700 series raceway** is recommended in scenarios where power and data cannot be recessed.



1. **FOR CONCRETE BLOCK WALL** - The 3/4" plywood will need to be installed over the finished concrete block wall surface, power and data, our strong preference is for these to be recessed. If that's not feasible, the DM package outlines an alternative solution: using Legrand Wiermond surface-mounted boxes attached directly to the concrete block. However, please note that the associated surface-mounted raceway will also be exposed, which may not be ideal from an aesthetic standpoint.
2. **REPAIR, PATCH, PAINT WALLS**
3. Please refer DM drawing for more specification.
4. Remove / relocate existing Board if present in the wall – Coordinate with Project Coordinator.
5. maintain cleanliness before and after work.



COMMUNITY BOARD C2-10  
L1-08 WALL



**CENTENNIAL**  
**COLLEGE**

PROJECT	PROJECT No.
990	
DATE	CHECKED BY
JULY 3, 2025	
SCALE	
DRAWING No.	